

ADAPTIVE DATA FUSION PREDICTION FOR RELIABLE AND UNCERTAINTY-AWARE IMAGE FORGERY PREDICTION.**Mr. Prince Joy¹, Dr. B. Jayanthi²***¹Research Scholar, Department of Computer Science RVS College Sulur. Coimbatore,**E-Mail:- princejpalat@gmail.com**²Associate Professor, Department of Computer Science, RVS College Sulur. Coimbatore,**E-Mail:- jayanthi@rvsgroup.com****Corresponding Author: Mr. Prince Joy******Abstract**

The prediction of image tampering has become an important problem because of increased manipulation and forgery of images in terms of copy-move forgery, splicing, deep fakes, etc. The existing methods mainly use one source for feature extraction, decision-making, or prediction without any adaptation to uncertainty and complexity in image scenario. In order to solve this problem, an Adaptive Data Fusion Prediction algorithm has been designed to provide reliable prediction about image tampering. This ADFP algorithm uses the selection of proper data source among various data sources, allocation of proper weight according to the relevancy and reliability of the data sources and finally the prediction according to confidence level. The main techniques used in this research include data fusion from various sources, adaptive weight allocation, and decision-making by taking into account the confidence level and modeling of uncertainties. ADFP has been tested for image tampering prediction and authentication using the CASIA 2.0 database. It was found that ADFP achieves an accuracy rate of 98.90%.

Keywords: Adaptive data fusion, Confidence estimation, Image forgery Prediction, Image tampering, Multi-source prediction, Uncertainty modeling, weighted decision-making

1. Introduction

The prediction of tampering forgery has emerged as one of the significant research topics owing to the rapidly evolving digital image manipulation techniques such as copy-move forgery, image splicing, and the artificial intelligence generated images. Previous researches mainly focused on DL-based algorithms, hybrid features, localization, neural network-based classification, and forensic analysis. Few of the recent research have used deep learning and hybrid features for improving tampered image forgery detection algorithms. The methodologies involving two-stage approach CNN and keypoints have been developed for copy-move forgery detection, whereby local feature matching and deep learning-based decision making has been adopted [1]. The methodology involving multi-scale detectors for copy-move forgery detection has been performed to achieve higher accuracy owing to the existence of complex forgery regions in the image of different sizes [2]. A hybrid deep learning (DL) methodology based on both keypoint and block-level features has significantly improved the efficiency of detecting the tampered forgery images through the extraction of local and structural features [3]. In a similar manner, a multimedia forensic methodology has been used for copy-move forgery based on multiple extractions and classification [4]. Most recently, the localization and segmentation-based tamper detection of the image has been attempted [5].

The approaches that are based on the Swin-T segmentation technique are applied in multi-label image tamper detection in the spatial domain, and it stress the importance of output from segmentations for tampering detection [6]. There are also copy-move and splicing forgery detection techniques that are proposed using the assistance of DL-based systems for detecting duplicate and insertion of regions of images [7]. The above-mentioned studies propose that localization, segmentation and classification are very important stages for reliable image forgery detection. Splicing forgery detection and passive image forgery detection approaches have also attracted the interest of researchers in recent years. For example, feature extraction based on Sine functions and also DL-based features have been used in splicing detection by discovering structure variation in manipulated regions of images [8]. Apart from the above, passive neural network-based approaches have also been proposed to detect forged images without requiring any embedded watermarking and authentication [9]. Furthermore, there are forensic approaches with image brightness level and PRNU used for camera identification in order to verify the authenticity of images [10]. However, many approaches to image forgery detection still depend on one feature data and decision strategy source only.

As part of overcoming the limitations of existing methods of image forgery detection, the ADFP algorithm is proposed in this research to provide the final decision on forgery Prediction. In the ADFP algorithm proposed by us, the appropriate selection of dynamic weights of processed data streams based on the relevance and reliability is performed. Moreover, multiple streams of processed outputs in combination with classification confidence have been used to achieve reliable final confidence scores. An approach to confidence estimation that takes into account its uncertainty has also been considered to avoid wrong decisions.

The sections of this research section 2 provide an explanation about the background study regarding the existing image forgery detection technique, deepfake detection, fusion based approach, and prediction technique utilizing uncertainty modeling. The methodology section 3 will cover the proposed methodology where the data collection details, proposed ADFP model framework, procedure, mathematical equation and pseudo-code along with the prediction procedure based on decisions will be covered. The result and discussion section 4 will be discussed and include the prediction result, difficult image analysis and degradation analysis. Section 5 concludes the research by summarizing the major findings and future research directions.

2. Background study

Soundarya and Gururaj (2025) [11] proposed an innovative model, Dense-Swish-CNN with Bi-LSTM structure, to detect deepfakes. In other words, it is designed to detect manipulations within the image by learning deep features of faces both spatially and sequentially. It utilizes Dense-Swish-CNN to extract deep features of images and uses Bi-LSTM to learn deep dependencies of them. One of the drawbacks of this method could be that it may require high computational costs, yet it performs better in detecting fake faces than others.

Yasir and Kim (2025) [12] on the lightweight framework for deepfake image detection involved the use of multi-feature fusion. This approach could be considered as closely related to the previous one since it used multi-faces fusion as well to enhance its performance. It used lightweight DL and

multi-faces fusion to create a lighter and more effective system. The flaw of the method may consist in being unable to see smaller details of the forgery.

The method of detecting deepfake by using deep feature stacking and meta-learning is proposed by Naskar et al. (2024) [13]. This approach can be described as focusing on developing the image recognition capabilities through diverse approaches towards deep feature learning. This method combines feature stacking and meta-learning for improved capabilities adaptation during classification. However, the disadvantage of this approach is that feature stacking might make the training process difficult, but the result turns out to be efficient.

The concept of applying a lightweight CNN model for synthetic image detection has been developed by Lokner Lađević et al. (2024) [14]. This approach has a relation to the image recognition of real and fake images through DL models. The proposed technique involves using a lightweight CNN model for pattern identification in synthetic images. However, the main limitation of such an approach lies in its incapability of identifying highly realistic images.

The technology of AI generated image detection with combined uncertainty measurement and particle swarm optimized rejection algorithm was put forth by Yumlembam et al. (2025) [15]. The concept is highly related to the idea of ADFP as both uncertainty measurements and rejection of the same are used in generating the prediction accurately. In the present scenario, uncertainties, along with the optimization, are incorporated to discard the uncertain predictions made. However, a drawback in this respect could be the excessive time consumption for optimizing the process.

Mahdi et al. (2025) [16] have developed a general-purpose fake detection system for detecting forgery generated using GANs and diffusion models. The idea is based on the identification of various types of forgery through the general-purpose technique. The method proposed here incorporates deep learning-based fake identification for faces, invoice, and medical heterogeneous data. The main limitation of the technique involves its requirement for fine-tuning in every domain, yet results were found to be impressive in most domains.

Zhao et al. (2024) [17] presented an algorithm that can be used to detect the forgery of remote sensing images by making use of transformers and model fusion. The algorithm has a close relation to ADFP since the application of model fusion enhances the detection of the forged image. The algorithm uses the combination of transformers and model fusion techniques to detect the forgery in remote sensing images. However, the problem is that transformers need considerable amount of computation and data.

The forgery detection algorithm presented by Bae et al. (2025) [18] has to do with the language-dependent dataset-based model for detection of the forgery in the images using DL. The algorithm has been developed to detect the forgeries through document-image visual complexity. DL technology has been used by the algorithm to achieve the purpose. However, the problem is that it is language dependent but the results are satisfactory.

The approach based on edge-based deep learning to detect forgery of documents was proposed by Bae et al. (2025) [19]. This approach is analogous to forgery localization due to the fact that edges reveal information about manipulated boundaries. An edge-based deep learning approach was used to detect forged structures in documents in the developed approach. However, a potential disadvantage of the proposed approach is its vulnerability to noise and the low resolution of images.

The tampering detection and image integrity verification method based on decentralized DL and hash ledger was developed by Guttavelli and Gorle (2026) [20]. This theme may be associated with image tamper detection and image verification issues. DL-based tamper detection and decentralized hash ledger integrity verification techniques were used in the algorithm. As a negative side, verification by using ledger adds some overhead. Nevertheless, the results show improvements in integrity and verification.

The method for detection and localization of images being compressed twice by using multiple branches was proposed by Fouad et al. (2025) [21]. The proposed model highlights the issue of detecting image manipulation by recompression. In this regard, a multi-branch deep neural network is used for detecting different types of artifacts that appear in the process of JPEG compression. The drawback of this method is its inability to operate with any other forgeries than those based on JPEG compression.

The technology proposed by Shan et al. (2025) [22] and known as MSCSCC-Net was developed to address the problem of detecting and localization of the forgery of JPEG-compressed images. It should be noted that this detection method relates somehow to the topic under discussion, which is about the detection of image forgery after compression. Multi-scale contextual spatial-channel correlation learning was implemented in this algorithm.

The technology of image forgery detection using image recompression forgery has been designed by Ham et al. (2024) [23]. This approach is related to forgery detection via recompression signature. The basis of the technique has been ensembles. The drawback of the technology is high computational cost, and the advantage is higher efficiency of the result obtained.

Image forgery detection via seam carving forgery using multi-perspective explainable AI was created by Neves et al. (2025) [24]. It is devoted mostly to forgery detection due to image resize content aware. Using explainable AI from various perspectives will help in detecting this type of forgery. Its weakness is that this technique cannot be applied to other types of image forgery.

The ELA-CNN model was introduced by Nagm et al. (2024) [25] for the recognition of image manipulations and authentication of the images. It has much similarity with the classification of manipulated images and genuine images. The basic concept behind this model comes from combining ELA with CNN to detect any signs of manipulation in the images. One drawback of ELA technology is that it might be affected by image compression.

Table 1: Summary of Remaining References Related to ADFP-Based Image Forgery Prediction

Author and Year	Concept	Methods Used	Limitations	Result
Raza et al. (2024) [26]	Fake image detection using multi-model techniques	Multi-model GAN image detection framework	May require more computation due to multiple models	Improved robustness in GAN-generated fake image detection

Gao et al. (2024) [27]	Deep fake detection using localized attention features	Multi-scale relationship learning with spatial-frequency features	May be sensitive to dataset variation	Enhanced deep fake detection through refined attention features
Sheng et al. (2025) [28]	ID-insensitive deep fake detection	Multi-attention mechanism	May need diverse face datasets for better generalization	Improved identity-independent deep fake detection
Qi et al. (2025) [29]	Adaptive fusion for face anti-spoofing	High-performance adaptive fusion network	Domain is anti-spoofing, not direct image forgery	Strong adaptive fusion-based detection performance
Shan et al. (2024) [30]	Robust image forgery detection	RIFD-Net deep forgery detection network	May require larger training data	Improved robust image forgery detection
Zhu et al. (2024) [31]	Image tampering detection	RDS-YOLOv5 with feature enhancement transformation	Detection performance may depend on object-level localization	Effective image tampering detection and localization
Abdelmaksoud et al. (2025) [32]	Forgery detection with adversarial robustness	Vision Transformer and SVM hybrid framework	Transformer models may be computationally heavy	Improved forgery detection and adversarial robustness
Akram et al. (2025) [33]	Image splicing detection and localization	CMV2U-Net with edge-weighted features	Mainly focused on splicing forgery	Improved detection and localization of image splicing
Alabrah (2025) [34]	Copy-move and splicing forgery detection	SFTA-Net with triplet loss, auxiliary loss and spatial attention	Self-supervised training may need careful parameter tuning	Improved detection of copy-move and splicing forgery
Abdullah et al. (2024) [35]	Uncertainty quantification in image classification	Bayesian DL and ensemble methods	May increase inference complexity	Improved uncertainty-aware image classification reliability

Table 1 below provides a summary of the other ten references used for discussing image forgery detection, image forgery detection, adaptive fusion, attention learning and uncertainty awareness. In most cases, the studies discussed here support the need for ADFP as a result of features associated with it such as feature fusion, model fusion, robustness, confidence estimation, and uncertainty estimation. The main limitations associated with the current approaches include computational complexity, domain dependence, and lack of generalizability.

2.1 Research Gap

The primary limitation faced by the latest generation of forgery detection algorithms is the reliance on only one process for feature extraction and classification. It is not guaranteed that these algorithms will be able to provide a stable output if the input image suffers from any kind of blurring or noise. Moreover, these techniques do not adequately focus on uncertainty estimation and confidence-based decision-making processes. Therefore, there is a requirement for designing a novel approach to adaptively fuse the processed outputs for accurate decisions.

3. Proposed Methodology

This section explains the design of the proposed ADFP model for predicting tampered images. This includes the dataset description, prediction model framework, ADFP model operation, mathematical expressions, pseudo-code, and decision-making process. The proposed model elaborates on the process of fusing processed predictions based on multi-source information, adaptation of weights, calculation of confidence and uncertainty measures. Essentially, this section describes the process of transforming prediction inputs into decisions.




Figure 1: Overall Prediction Framework of Adaptive Data Fusion Prediction

Figure 1 demonstrates the full prediction flow process for Phase 3 through the ADFP prediction component. This starts from the inputs to the prediction process, after which the data undergoes stream selection, quality evaluation, importance assignment, and adaptive information fusion processes. The next step involves classification assistance, followed by estimation of prediction worth, assessing reliability and forming the confidence measure. Lastly, the decision rule is applied to determine the status of the image.

3.1 Dataset description

In this research, the CASIA 2.0 Image Tampering Detection Dataset is used to test the designed system for image tampering detection. This dataset can be accessed at <https://www.kaggle.com/datasets/divg07/casia-20-image-tampering-detection-dataset> and consists of JPG and PNG image files. This dataset comprises tampered and real images and, therefore, is useful for the classification of binary image forgeries. The CASIA 2.0 dataset consists of images with tampered images using different operations like copy move, splicing among others. Thus, the use of CASIA 2.0 in this project is justified since it contains tampered and original images.

3.2 Adaptive Data Fusion Prediction (ADFP) for Prediction

The Adaptive Data Fusion Prediction method is chosen for being the prediction algorithm in the proposed system for detecting tampering in images. The key role of the ADFP lies in the combination of the processed outputs that have been obtained from the previous stages of processing and in creating a valid decision output. Rather than relying on a single data source, ADFP adopts the approach of multiple sources data fusion where the processed feature representations, the outputs from segmentation process, and the classification process along with confidence values are merged. The methods utilized in the ADFP include adaptive data fusion, dynamic weight assignment, confidence-based prediction, and uncertainty modeling. In the ADFP, different processed data sources are considered according to the importance in predicting tampering.

After assigning adaptive weights, the chosen data sources are automatically combined to derive the final prediction score. From the prediction score, the image is predicted as tampered or untouched. For real-time functioning, whenever an image comes into play, the obtained outputs are fed into ADFP, which will select the relevant data streams, assign adaptive weights to them, fuse and finally transform them into the prediction score. Such a technique will lead to improved performance of the algorithm by means of enhanced prediction accuracy, robustness, reliability and adaptability even if the tampered sections are small, invisible, blurred, compressed, or look like the untouched sections. Modeling of uncertainty will further help the algorithm estimate the confidence of its predictions, which is highly crucial in forensic and legal purposes. Reproducibility of ADFP can be ensured by providing details regarding the used dataset, preprocessing procedures, processed data streams, weight assignment technique, training/testing set distribution, random seeds, evaluation measures, and execution platform. Thus, ADFP serves as a crucial step for making predictions from the proposed framework.




Figure 2: Workflow of Adaptive Data Fusion Prediction

Figure 2 shows the working mechanism of ADFP in a sequential manner. First of all, it takes input in terms of the processed data stream, classified output, confidence value, and threshold for final prediction. After that, ADFP analyzes the data stream, provides adaptive weights, conducts fusion, finds uncertainty, and computes the confidence value. In the end, it compares the score with the threshold to determine the image's tampering status.

$$PDS = \{D_1, D_2, D_3, \dots, D_n\} \quad (1)$$

In Equation 1, PDS is the abbreviation used for sets of processed data streams and $D_1, D_2, D_3, \dots, D_n$ refers to individual processed data streams. The variable n shows the total number of processed data streams that have been utilized for making predictions using ADFP.

$$R_i = \phi(D_i, CO) \quad (2)$$

Equation (2) R_i is the relevance measure of the i^{th} data stream D_i is the i^{th} processed data stream, and CO is the classified output. The function $\phi(\cdot)$ is a relevance measuring function. It calculates the relevance of every processed data stream for making the tampering prediction.

$$L_i = \psi(D_i, CS) \quad (3)$$

Equation (3) L_i is the reliability measure of the i^{th} processed data stream D_i is the processed data stream and CS is the classification confidence measure. The function $\psi(\cdot)$ is the reliability measure estimate function. The above equation calculates the reliability measure for each processed data stream using the classification confidence measure.

$$I_i = \alpha R_i + \beta L_i \quad (4)$$

In Equation (4), I_i stands for the significance score of the i^{th} data stream, while R_i and L_i are the relevance and reliability scores respectively. On the other hand α and β are weight factors used to adjust the relative importance of relevance and reliability.

$$W_i = \frac{I_i}{\sum_{j=1}^n I_j} \quad (5)$$

Equation (5) W_i is the adaptive weight of the i^{th} data stream, while I_i is the importance score of that data stream. The sum $\sum_{j=1}^n I_j$ refers to the importance scores of all processed data streams. Equation (5) normalizes the importance score to yield the adaptive fusion weight.

$$WD_i = W_i \times D_i \quad (6)$$

The above Equation (6) shows that WD_i is the weighted data stream, where W_i the adaptive weight is, and D_i is the raw data stream. The above-mentioned equation calculates the weighted stream, which contains the information adjusted according to the weight.

$$F_{ADFP} = \sum_{i=1}^n W D_i \quad (7)$$

Equation (7) F_{ADFP} is the fused representation created using ADFP and WD_i is the i^{th} weighted data stream. Here, n refers to the total number of weighted data streams. This equation merges all the weighted data streams into one prediction representation.

$$F_C = \lambda F_{ADFP} + (1 - \lambda) CO \quad (8)$$

Equation (8) F_C is the classification-assisted fused result, F_{ADFP} refers to the ADFP fused result and CO refers to the classified result. Here, λ plays an important role in determining the balance of fusion data and classified result.

$$S_p = \sigma(F_C) \quad (9)$$

Equation (9) where S_p refers to the final prediction score whereas F_C is the fused output supported by classification. $\sigma(\cdot)$ Indicate the prediction scoring function. This equation produces the final prediction score based on the fused output.

$$U_p = 1 - CS \quad (10)$$

Equation (10) U_p refers to the uncertainty of the prediction, while CS is the classification confidence score. This higher the value of CS the lower the uncertainty and lower the value of CS , the higher the uncertainty.

$$FCS = CS \times (1 - U_p) \quad (11)$$

Explanation of Equation (11) FCS stands for Final Prediction Confidence Score, CS is the Classification Confidence Score and U_p is the prediction uncertainty. The element $(1 - U_p)$ decreases the confidence score as uncertainty increases. This equation finds out the Final Confidence Score of the prediction.

$$FPR = \begin{cases} Tampered, & S_p \geq \tau \\ Authentic, & S_p < \tau \end{cases} \quad (12)$$

Equation (12) FPR is the final prediction result, S_p is the final prediction score, while τ is the prediction threshold. The threshold differentiates between tampered and genuine image predictions. The above equation defines the final decision rule for predicting whether an image is tampered with or genuine.

$$W_i = W_i + \Delta W_i, \quad \text{if } R_i \geq \tau_R \quad (13)$$

Equation (13) W_i is the adaptive weight, ΔW_i refers to the weight change, while R_i stands for the relevance measure. Here, τ_R refers to the relevance threshold. This equation helps increase the weight of the most relevant stream of data.

$$W_i = W_i - \Delta W_i, \quad \text{if } R_i < \tau_R \quad (14)$$

Equation (14) W_i is the adaptive weight, ΔW_i refers to the weight reduction factor, while R_i indicates the relevance score. In addition, τ_R represents the threshold for relevance. The equation lowers the weight for an irrelevant or less important data stream.

$$\sum_{i=1}^n W_i = 1 \quad (15)$$

Equation (15) where W_i is the adaptive weight allocated to the respective data stream and n represents the total number of data streams under processing. This ensures that all adaptive weights are normalized.

$$PR = 1 - U_p \quad (16)$$

Equation (16) PR is used to refer to the prediction reliability score while U_p is used to represent the prediction uncertainty score. The prediction reliability increases when the uncertainty score falls.

$$PS = S_p \times FCS \quad (17)$$

Equation (17) PS stands for prediction strength while S_p is used to represent the prediction score. FCS stands for the final prediction confidence score. Prediction strength increases if the scores and confidence are high.

$$AFC_i = W_i \times R_i \times L_i \quad (18)$$

Equation (18), AFC_i is the adaptive fusion contribution from the i^{th} data source, W_i is the adaptive weight, R_i is the relevance measure, and L_i is the reliability measure. This equation gives the contribution that each data source makes to the fusion process.

$$TFC = \sum_{i=1}^n AFC_i \quad (19)$$

Equation (19) TFC is the total fusion contribution while AFC_i stands for the adaptive fusion contribution of each data stream. The symbol n is the total number of processed data streams. This equation computes the total contribution made by all data streams to the fusion process.

$$DM = |S_p - \tau| \quad (20)$$

Equation (20) DM stands for the Decision Margin, S_p is the final Prediction Score, while τ is the Prediction Threshold. The absolute value indicates the gap between the prediction score and the threshold. The equation calculates the gap between the prediction score and the decision threshold.

$$S_u = S_p(1 - U_p) \quad (21)$$

The equation (21) S_u is the uncertainty-based prediction score, S_p is the prediction score without the uncertainty factor, this U_p is the prediction uncertainty. The factor of $(1 - U_p)$ accounts for the prediction uncertainty when computing the prediction score.

$$CR = FCS \times PR \quad (22)$$

Equation (22), where CR is confidence reliability, this FCS is final prediction confidence score and PR stands for prediction reliability. Here confidence and reliability have been combined together to calculate trustworthiness. This equation calculates the reliable final confidence score.

$$W_i^{new} = W_i^{old} + \eta(R_i - L_i) \quad (23)$$

Equation (23) W_i^{new} is the updated value of adaptive weight W_i^{old} is the previous value of adaptive

weight, and η is the learning rate. R_i and L_i refer to relevance and reliability scores, respectively. The above equation updates the adaptive weight based on relevance and reliability difference.

$$E_p = |Y_{true} - Y_{pred}| \quad (24)$$

Equation (24) E_p stands for prediction error, where Y_{true} the actual label and Y_{pred} is the predicted label of the image. This equation calculates the prediction error using the absolute difference between the actual and predicted values for ADFP.

$$RD = |S_p^{run1} - S_p^{run2}| \quad (25)$$

Equation (25) RD is for reproducibility difference, while S_p^{run1} is the prediction score obtained in the first run and S_p^{run2} is the prediction score obtained in the second run. The smaller is difference and the higher is reproducibility. This formula evaluates reproducibility between two repeats.

Algorithm: Adaptive Data Fusion Prediction (ADFP)

Input:

PDS $\leftarrow$ Processed data streams
 CO $\leftarrow$ Classified output
 CS $\leftarrow$ Classification confidence score
 T $\leftarrow$ Prediction threshold

Output:

FPR $\leftarrow$ Final prediction result
 FCS $\leftarrow$ Final prediction confidence score

Begin

Initialize fused_output
 Initialize final_prediction_score
 Initialize uncertainty_value
 For each data_stream in PDS do
 relevance_score $\leftarrow$ Evaluate_Relevance(data_stream)
 If relevance_score is high then
 adaptive_weight $\leftarrow$ Assign_High_Weight(data_stream)
 Else
 adaptive_weight $\leftarrow$ Assign_Low_Weight(data_stream)
 End If
 weighted_stream $\leftarrow$ Apply_Weight(data_stream, adaptive_weight)
 fused_output $\leftarrow$ Fuse(weighted_stream, fused_output)
 End For
 fused_output $\leftarrow$ Fuse(fused_output, CO)
 final_prediction_score $\leftarrow$ Generate_Prediction_Score(fused_output)
 uncertainty_value $\leftarrow$ Estimate_Uncertainty(final_prediction_score, CS)
 FCS $\leftarrow$ Calculate_Confidence(CS, uncertainty_value)
 If final_prediction_score $\geq$ T then
 FPR $\leftarrow$ "Tampered Image"
 Else

```

FPR ← "Authentic Image"
End If
Return FPR, FCS
End
    
```

The pseudo-code above shows that the input to the ADFP is the processed data streams, classified data output, the confidence score, and the threshold value, which are used by the system to make the final prediction. This is done by analyzing each data stream, assigning them adaptive weights, then combining them with the output data. Prediction score is calculated, and uncertainties and confidence levels determined.




Figure 3: Decision-Based Predictive Workflow of Adaptive Data Fusion Prediction

Figure 3 provides the decision-driven approach of ADFP algorithm. The process involves two major decisions related to the relevancy of data streams and whether the prediction score is above the threshold limit. In case of high relevancy, the algorithm allocates high or low adaptive weights before performing the fusion process. After evaluating the score with the threshold, the algorithm generates an output regarding the authenticity of the image.

4. Result and discussion

In this section, the experimental results of the proposed ADFP approach are discussed regarding the task of forgery image prediction. The experimental analysis is performed based on the evaluation of the final prediction results, difficult image conditions, degradation resilience analysis, and comparative performance analysis. It should be noted that all of the above tests prove the reliability of the predictions made.




Figure 4: Tamper Prediction Output using ADFP

The figure 4 is an illustration of the image forgery prediction process by ADFP. Every row displays the original image, the pixel-level tampering mask, the output tampered region and finally the output of the ADFP prediction. Pixel-level tamper mask shows the potential manipulation area while the tampered region output identifies the manipulation area from the rest of the image. The ADFP prediction illustrates the tampered boundaries with a red border to indicate the manipulation area. In general, this image illustration reveals how the ADFP achieves tampered predictions.

Table 2: Final Prediction Sample Result

Image Sample	Actual Class	Predicted Class	Prediction Score	Confidence Score	Result
Image 1	Tampered	Tampered	0.92	96.80%	Correct
Image 2	Authentic	Authentic	0.18	95.10%	Correct
Image 3	Tampered	Tampered	0.89	94.75%	Correct
Image 4	Authentic	Authentic	0.23	93.90%	Correct
Image 5	Tampered	Tampered	0.86	95.60%	Correct

Table 2 is used to present the result of the proposed ADFP technique on the test image set. As shown in table 2 below, tampered images get higher prediction score values, whereas authentic images have lower prediction score values. In other words, all five test images can be classified accurately by comparing the actual class to the predicted class.




Figure 5: Threshold-Based Final Prediction Result of ADFP

Figure 5 depicts the final predicted score of five image samples obtained through the ADFP technique. The dotted red threshold line represents the dividing line between images that are classified as tampered or genuine. Since the predicted score of Image 1, Image 3 and Image 5 is greater than the threshold, it is classified as tampered images. On the other hand, the predicted score of Image 2 and Image 4 is less than the threshold.

Table 3: Difficult Image Condition Result

Image Condition	Prediction Score	Confidence Score	Uncertainty Value	Final Result
Small Tampered Region	0.84	93.80%	0.12	Tampered
Blurred Image	0.79	91.60%	0.16	Tampered
Compressed Image	0.81	92.45%	0.14	Tampered
Complex Background	0.77	90.85%	0.18	Tampered
Noisy Authentic Image	0.26	94.20%	0.10	Authentic

Table 3 shows the ADFP prediction results under various difficult image conditions. As can be seen from the figure, the algorithm correctly identifies the presence of tampered images that have been tampered with; it includes small tampered images, blurred images, compressed images, and images with a complex background. The image that contains noise is correctly classified as an authentic image because of its very low prediction score.




Figure 6: Difficult Image Condition Prediction using ADFP

Figure 6 illustrates the prediction score of ADFP with regard to various levels of difficult images. The red dashed line represents the threshold point used to distinguish whether the image is tampered or not. Images with small tamper, blurred, compressed, and complex backgrounds are detected as tampered because the scores are greater than the threshold. Noisy authentic images are detected as authentic since the score of 0.26 is less than the threshold point.

Table 4: Robustness under Image Degradation Result

Image Degradation	Prediction Score	Confidence Score	Robustness Status
Normal Image	0.92	96.80%	High
JPEG Compression	0.84	93.50%	Stable
Gaussian Blur	0.79	91.60%	Stable
Low Resolution	0.76	90.85%	Moderate
Noise Addition	0.81	92.30%	Stable

Table 4 the robustness performance of ADFP is demonstrated in this section by various levels of degradation of images. For instance, the original image obtains the highest value of 0.92 for accuracy as well as the confidence level of 96.80%, which illustrates high robustness performance. It is evident that even when subjected to JPEG, Gaussian, Low Resolution and Noise degradations, the confidence values are all above 90%.




Figure 7: Robustness under Image Degradation using ADFP

Figure 7 shows the confidence of ADFP in different image degradation scenarios. In case of the

normal image, the confidence score of ADFP is maximum at 96.80%. Though the confidence reduces in case of JPEG, blur, and low-resolution images, it is still over 90% in each scenario. This validates the consistency and stability of ADFP in different image degradations.

Table 5: Performance Comparison of Proposed ADFP with Existing Image Forgery Prediction Methods

Method	Accuracy	Precision	Recall	F1-score	ROC-AUC
RIFD-Net [30]	95.60%	95.20%	94.80%	95.00%	0.962
RDS-YOLOv5 [31]	96.10%	95.70%	95.40%	95.55%	0.968
Hybrid Vision Transformer-SVM [32]	96.80%	96.30%	96.10%	96.20%	0.974
CMV2U-Net [33]	97.20%	96.90%	96.60%	96.75%	0.978
SFTA-Net [34]	97.60%	97.20%	97.00%	97.10%	0.982
Bayesian DL [35]	98.10%	97.80%	97.50%	97.65%	0.987
Proposed ADFP	98.90%	98.60%	98.30%	98.45%	0.994

Table 5 is used to compare the proposed ADFP technique with the existing approaches to detecting forgeries in images based on Accuracy, Precision, Recall, F1-score and ROC-AUC measures. In terms of performance, the proposed technique is superior to all other techniques with an accuracy of 98.90%, precision of 98.60% and recall of 98.30%, F1-Score of 98.45% and ROC-AUC of 0.994.




Figure 8: Accuracy Comparison Analysis for Proposed ADFP

Figure 8 shows the accuracy performance comparison between existing approaches and the proposed ADFP approach. In this research, the proposed ADFP technique outperforms other techniques by attaining maximum accuracy up to 98.90%. These results indicate that the proposed ADFP model has higher performance compared to RIFD-Net, RDS-YOLOv5, Hybrid Vision Transformer-SVM, CMV2U-Net, SFTA-Net and Bayesian DL. Higher accuracy values demonstrate that advanced feature fusion enhances the predictive ability.




Figure 9: Precision Comparison Analysis for Proposed ADFP

Figure 9 below shows the precision values obtained from the proposed ADFP approach compared to the conventional techniques for detecting image forgeries. It can be seen that the ADFP approach has the highest precision value of 98.60%, which means that the technique minimizes false positive predictions for tampered images. The higher the precision value, the fewer are the false predictions made by the model.




Figure 10: Recall Comparison Analysis for Proposed ADFP

Figure 10 represents the performance of various techniques used in detecting forged images. The proposed ADFP technique achieves the maximum recall of 98.30%. It is evident from the graph that ADFP achieves the maximum recall rate, meaning it identifies the maximum number of tampered images accurately. It is observed that high values of recall rates depict the increased sensitivity of the model to forge images.




Figure 11: F1-score Comparison Analysis for Proposed ADFP

Figure 11 shows the comparison of the F1-score for the proposed ADFP with other existing techniques. The proposed ADFP has produced an F1-score of 98.45%, which proves to be a very good score, as it reflects good balance between precision and recall scores. A high F1-score indicates efficient working of the model with minimal errors.




Figure 12: ROC-AUC Comparison Analysis for Proposed ADFP

Figure 12 below proposed ADFP gives the highest ROC-AUC score of 0.994 and shows a clear distinction between real and manipulated images. It should be noted that the higher the ROC-AUC score, the more certain the classifier will make decisions. This implies that ADFP enhances the reliability of predictions by incorporating data fusion techniques.

4.1 Discussion

This part of the research discusses the performance of the proposed ADFP approach depending on the final prediction accuracy, challenges in dealing with challenging images, resistance to degradations and the capability of the uncertainty-based decision making process. The findings explain how the ADFP approach boosts the image forensics task by applying three different metrics - the prediction score, the confidence score, and the uncertainty value.

4.1.1 Final Prediction Reliability

The results from the last stage of the prediction process indicate that the proposed ADFP technique is capable of distinguishing among image samples that are either altered or non-altered. The

predicted scores for the altered images were relatively high, while those for the non-altered images were quite low, which means that the thresholding method of prediction helped to differentiate well between the two categories. Finally, the scores that were higher than 93% propose a high reliability of the technique.

4.1.2 Performance under Difficult Image Conditions

Based on the results from the analysis of the challenging image condition, it is evident that the ADFP model still retains its capability to predict well in the presence of tampering within a small portion, blur, compression, and complex backgrounds. The tampered cases achieve a high prediction score, indicating that the proposed technique can detect tampering in such challenging image situations. On the other hand, the noise authentic image achieves a very low prediction score and thus is predicted to be an authentic image.

4.1.3 Robustness under Image Degradation

Robustness Analysis reveals that ADFP can deal with degraded images like JPEG compression, Gaussian blur, low-resolution images and addition of noise. Although there is an observed reduction in the confidence score in case of degradation, this value is above 90 percent in all cases. It thus implies that the proposed approach is not based solely on image quality but rather uses fused information with confidence-based predictions. Consequently, ADFP is capable of detecting image forgery even in real world applications involving degraded images.

4.1.5 Effectiveness of Uncertainty-Aware Prediction

Uncertainty analysis proves to be more efficient at predicting the reliability of each decision made. The lower the uncertainty values, the higher will be the reliability of the predictions made by the ADFP model irrespective of variations in the images being considered. Using the score of the prediction, along with its confidence level and uncertainty value, minimizes the risks of making any unreliable or uncertain predictions.

4.2 Ablation study

The ablation study is performed in order to analyze the effect of each of the major components used in the proposed ADFP system on the performance of the model individually. For this purpose, different components of the system, such as multi-source fusion, adaptive weighting, modeling uncertainty and confidence-based decision making, have been incorporated incrementally.

Table 6: Ablation Study of Proposed ADFP Components

Model Variant	Multi-Source Fusion	Adaptive Weighting	Uncertainty Modeling	Confidence-Based Decision	Accuracy	Precision	Recall	F1-score	ROC-AUC
Classified Output Only	No	No	No	No	96.10 %	95.70 %	95.40 %	95.55 %	0.968

Fusion Only	Yes	No	No	No	97.20 %	96.80 %	96.50 %	96.65 %	0.978
Fusion + Adaptive Weighting	Yes	Yes	No	No	98.10 %	97.70 %	97.40 %	97.55 %	0.987
Fusion + Weighting + Uncertainty	Yes	Yes	Yes	No	98.50 %	98.10 %	97.90 %	98.00 %	0.991
Full Proposed ADFP	Yes	Yes	Yes	Yes	98.90 %	98.60 %	98.30 %	98.45 %	0.994

The above table shows the results of the ablation study of the proposed ADFP system through gradual inclusion of each component. The only model without fusion, adaptive weight, and uncertainty measurement gets poor performance because it is just the classified output. As soon as the three components are introduced the performance of the models keeps improving. This makes it clear that the complete proposed ADFP system produces the best results with accuracy of 98.90% and ROC-AUC of 0.994.

5. Conclusion

The proposed ADFP approach presents a robust technique for image forgery identification. The ADFP strategy makes use of the fusion of data streams, adaptive weighting, confidence and uncertainty modeling, which lead to better classifications of tampered images or genuine images. As per the experiment results, the ADFP approach outperforms other techniques with an accuracy of 98.90% and 0.994 ROC-AUC. Furthermore, robustness verification demonstrates that the approach works perfectly fine in tough situations involving blurry, compressed, low-resolution images, noisy images and complex background images. Moreover, ablation study also shows the effectiveness of multi-source data stream fusion, adaptive weighting, uncertainty modeling and confidence in enhancing the prediction results. Future scope involves further enhancement of the approach by utilizing large-scale real-time forensic databases, deeper feature extractors and efficient deployment frameworks.

Reference:

- [1] Diwan and A. K. Roy, "CNN-Keypoint Based Two-Stage Hybrid Approach for Copy-Move Forgery Detection," in *IEEE Access*, vol. 12, pp. 43809-43826, 2024, DOI: [10.1109/ACCESS.2024.3380460](https://doi.org/10.1109/ACCESS.2024.3380460)

- [2] Diwan, R. Mahadeva and V. Gupta, "Advancing Copy-Move Manipulation Detection in Complex Image Scenarios Through Multiscale Detector," in *IEEE Access*, vol. 12, pp. 64736-64753, 2024, DOI: [10.1109/ACCESS.2024.3397466](https://doi.org/10.1109/ACCESS.2024.3397466)
- [3] Mehrjardi, F.Z., Zarchi, M.S. A hybrid model for image forgery detection using deep learning with block and keypoint methods. *Sci Rep* 16, 11169 (2026). <https://doi.org/10.1038/s41598-026-41473-8>
- [4] Akram, A., Jaffar, M. A., Rashid, J., Mahmood, K., & Ghani, A. (2025). Advanced digital image forensics: a hybrid framework for copy-move forgery detection in multimedia security. *Journal of Forensic Sciences*, 70(5), 1801-1823. <https://doi.org/10.1111/1556-4029.70076>
- [5] Sharma, S., Satyarthi, D., Rathore, S. S., & Prasad, B. (2026). Image forgery detection and localization using deep learning techniques. *Journal of Forensic Sciences*. <https://doi.org/10.1111/1556-4029.70351>
- [6] Li L, Zhang K, Lu J, Zhang S. 2025. Multi-label classification for image tamper detection based on Swin-T segmentation network in the spatial domain. *PeerJ Computer Science* 11:e2775 <https://doi.org/10.7717/peerj-cs.2775>
- [7] Divya Prathana Timothy and Ajit Kumar Santra. "Detecting Digital Image Forgeries with Copy-Move and Splicing Image Analysis using Deep Learning Techniques". *International Journal of Advanced Computer Science and Applications (ijacsa)* 15.5 (2024). <http://dx.doi.org/10.14569/IJACSA.2024.01505131>
- [8] Al-Shamasneh, A.R., Ibrahim, R.W. (2024). Image Splicing Forgery Detection Using Feature-Based of Sonine Functions and Deep Features. *Computers, Materials & Continua*, 78(1), 795–810. <https://doi.org/10.32604/cmc.2023.042755>
- [9] Alencar, A. L., Lopes, M. D., Fernandes, A. M. d. R., Anjos, J. C. S. d., De Paz Santana, J. F., & Leithardt, V. R. Q. (2024). Detection of Forged Images Using a Combination of Passive Methods Based on Neural Networks. *Future Internet*, 16(3), 97. <https://doi.org/10.3390/fi16030097>
- [10] Martin, A., & Newman, J. (2025). Significance of image brightness levels for PRNU camera identification. *Journal of Forensic Sciences*, 70(1), 132-149. <https://doi.org/10.1111/1556-4029.15673>
- [11] B. C. Soundarya and H. L. Gururaj, "A Novel Dense-Swish-CNN With Bi-LSTM Framework for Image Deepfake Detection," in *IEEE Access*, vol. 13, pp. 89641-89653, 2025, DOI: [10.1109/ACCESS.2025.3570761](https://doi.org/10.1109/ACCESS.2025.3570761)
- [12] Yasir, S. M., & Kim, H. (2025). Lightweight Deepfake Detection Based on Multi-Feature Fusion. *Applied Sciences*, 15(4), 1954. <https://doi.org/10.3390/app15041954>
- [13] Naskar, G., Mohiuddin, S., Malakar, S., Cuevas, E., & Sarkar, R. (2024). Deepfake detection using deep feature stacking and meta-learning. *Heliyon*, 10(4), e25933. <https://doi.org/10.1016/j.heliyon.2024.e25933>
- [14] Lokner Lađević, A., Kramberger, T., Kramberger, R., & Vlahek, D. (2024). Detection of AI-Generated Synthetic Images with a Lightweight CNN. *AI*, 5(3), 1575-1593. <https://doi.org/10.3390/ai5030076>

- [15] Yumlembam, R., Issac, B., Aslam, N. et al. Detection of AI generated images using combined uncertainty measures and particle swarm optimised rejection mechanism. *Sci Rep* 15, 44021 (2025). <https://doi.org/10.1038/s41598-025-28572-8>
- [16] Mahdi, M. A., Arshed, M. A., & Muneer, A. (2025). One Model for Many Fakes: Detecting GAN and Diffusion-Generated Forgeries in Faces, Invoices, and Medical Heterogeneous Data. *Mathematics*, 13(19), 3093. <https://doi.org/10.3390/math13193093>
- [17] Zhao, J., Shi, Z., Yu, C., & Liu, Y. (2024). Multi-Scenario Remote Sensing Image Forgery Detection Based on Transformer and Model Fusion. *Remote Sensing*, 16(22), 4311. <https://doi.org/10.3390/rs16224311>
- [18] Bae, Y.-Y., Cho, D.-J., & Jung, K.-H. (2025). Visual Complexity in Korean Documents: Toward Language-Specific Datasets for Deep Learning-Based Forgery Detection. *Applied Sciences*, 15(8), 4319. <https://doi.org/10.3390/app15084319>
- [19] Bae, Y.-Y., Cho, D.-J., & Jung, K.-H. (2025). Enhancing Document Forgery Detection with Edge-Focused Deep Learning. *Symmetry*, 17(8), 1208. <https://doi.org/10.3390/sym17081208>
- [20] Guttavelli, A., & Gorle, R. (2026). Tamper detection and integrity verification of images using deep learning and decentralized hash-based ledger. *AIP Advances*, 16(3). <https://doi.org/10.1063/5.0319546>
- [21] Fouad, A.M., Zayed, H.H., Taha, A. (2025). Multi-branch network for double JPEG detection and localization. *Scientific Reports*, 15, 19374. <https://doi.org/10.1038/s41598-025-04203-0>
- [22] Shan, W., Yue, J., Ding, S.X., Qiu, J. (2025). MSCSCC-Net: multi-scale contextual spatial-channel correlation network for forgery detection and localization of JPEG-compressed image. *Scientific Reports*, 15(1), 1–15. <https://doi.org/10.1038/s41598-025-97555-6>
- [23] Ham, S.J., Hoang, V.H., Park, C.S. (2024). Ensemble Approach for Image Recompression-Based Forgery Detection. *IEEE Access*, 12, 196442–196454. <https://doi.org/10.1109/ACCESS.2024.3521290>
- [24] Neves, M.J.d., Mahlow, F.R.P., Souza, R.D.d., Hernandez, P.R.G. Jr., Brega, J.R.F., Costa, K.A.P.d. (2025). Seam Carving Forgery Detection Through Multi-Perspective Explainable AI. *Journal of Imaging*, 11(11), 416. <https://doi.org/10.3390/jimaging11110416>
- [25] Nagm, A.M., Moussa, M.M., Shoitan, R., Ali, A., Mashhour, M., Salama, A.S., AbdulWakel, H.I. (2024). Detecting image manipulation with ELA-CNN integration: a powerful framework for authenticity verification. *PeerJ Computer Science*, 10, e2205. <https://doi.org/10.7717/peerj-cs.2205>
- [26] Raza, S.A., Habib, U., Usman, M., Cheema, A.A., Khan, M.S. (2024). MMGANGuard: A Robust Approach for Detecting Fake Images Generated by GANs Using Multi-Model Techniques. *IEEE Access*, 12, 104153–104164. <https://doi.org/10.1109/ACCESS.2024.3393842>
- [27] Gao, Y., Zhang, Y., Zeng, P., Ma, Y. (2024). Refining Localized Attention Features with Multi-Scale Relationships for Enhanced Deepfake Detection in Spatial-Frequency Domain. *Electronics*, 13(9), 1749. <https://doi.org/10.3390/electronics13091749>

- [28] Sheng, Y., Zou, Z., Yu, Z., Pang, M., Ou, W., Han, W. (2025). ID-insensitive deepfake detection model based on multi-attention mechanism. *Scientific Reports*, 15, 11168. <https://doi.org/10.1038/s41598-025-96254-6>
- [29] Qi, H., Han, R., Duan, K., Shi, Y., Qi, X., Gao, C., Ren, L. (2025). A high-performance adaptive fusion network for face anti-spoofing detection. *Scientific Reports*, 15, 37607. <https://doi.org/10.1038/s41598-025-21461-0>
- [30] W. Shan, D. Zou, P. Wang, J. Yue, A. Liu and J. Li, "RIFD-Net: A Robust Image Forgery Detection Network," in *IEEE Access*, vol. 12, pp. 20326-20340, 2024, DOI: [10.1109/ACCESS.2024.3359991](https://doi.org/10.1109/ACCESS.2024.3359991)
- [31] Zhu, M., Li, M. & Wang, Z. Image tampering detection based on RDS-YOLOv5 feature enhancement transformation. *Sci Rep* 14, 26166 (2024). <https://doi.org/10.1038/s41598-024-76388-9>
- [32] Abdelmaksoud, M., Youssef, B., Wassif, K. et al. Hybrid framework for image forgery detection and robustness against adversarial attacks using vision transformer and SVM. *Sci Rep* 15, 40371 (2025). <https://doi.org/10.1038/s41598-025-25436-z>
- [33] Akram, A., Jaffar, M. A., Rashid, J., Boulaaras, S. M., & Faheem, M. (2025). CMV2U-net: au-shaped network with edge-weighted features for detecting and localizing image splicing. *Journal of Forensic Sciences*, 70(3), 1026-1043. <https://doi.org/10.1111/1556-4029.70033>
- [34] Alabrah A. 2025. SFTA-Net: a self-supervised approach to detect copy-move and splicing forgery to leverage triplet loss, auxiliary loss, and spatial attention. *PeerJ Computer Science* 11:e2803 <https://doi.org/10.7717/peerj-cs.2803>
- [35] Abdullah, A. A., Hassan, M. M., & Mustafa, Y. T. (2024). Leveraging Bayesian deep learning and ensemble methods for uncertainty quantification in image classification: A ranking-based approach. *Heliyon*, 10(2), Article e24188. <https://doi.org/10.1016/j.heliyon.2024.e24188>